



SPECIFICATION SHEET

ARC FLASH GO/RT COVERALL



Product Code:


CARC53OR

Selling UOM:

Each

Pack Size:

1

-  Anti Static
-  Arc Flash Protection
-  Cat 3 - High Risk
-  Fire Retardant
-  Hi Visibility
-  Protection for Welding and Allied Processes

- Fire Retardant, Hi Vis, Anti-static, ARC Flash Orange Coverall.
- GO/RT 3279 issue 8 2013 for use on or around railway lines.
- 310gsm 40% Modacrylic 24% Viscose, 20% Polyester, 10% Cotton, 4% Aramid, 2% Anti-static Fibre.
- 2 hip pockets.
- Large bellows pocket to each leg with hook and loop closure flap.
- Right leg mobile phone pocket with hook and loop closure flap.
- All pocket flaps with Retro-reflective tape feature.
- Internal knee pad pouches.
- Large qualifying icons on left leg pocket.
- Adjustable leg bellows.

- EN ISO 13688:2013 - General requirements for protective clothing
- EN ISO 20471:2013 Class 3 - Test method for high visibility - GORT 3279 Issue 8
- EN 1149-3:2004 - Anti Static - Test methods for measurements of charge decay
- EN 1149-5:2008 - Anti Static - Material performance and design requirements
- EN ISO 11611:2015 (Class 1 A1 A2) - Protective clothing for use in welding
- EN ISO 11612:2015 (A1 A2 B1 C1) - Protection against heat and flame

ARC FLASH

IEC 61482-2:2009 - Performance requirements and design requirements

EN 61482-1-2:2007 (Class 1 = 4kA) - Box Arc testing

EN 61482-1-1:2009 (ATPV = 16 Cal/cm²) - Open Arc testing

- Each garment style is independantly tested to both box and open ARC standards.
- Click ARC production is covered by article 11B certification.



Packaging Waste	Type	Units	Weight(g)	Length(mm)	Width(mm)	Height(mm)
Cardboard	Outer	1	960.00	520.00	510.00	320.00
Plastic	Inner	10	77.77			
Paper	Inner	10	8.33			
Carton Weight:			18.76kg			